

Dongyan-Alu

Code

DY-01-3584

Workbench

2000T

Technical drawing of a perforated metal plate. The drawing shows a series of vertical rectangular slots. Key dimensions are labeled: total width 301, total height 51.5, slot width 4, distance between slot centers 28-1.8, slot depth 1.8, base thickness 10, distance between base holes 2.6, and distance between base holes 28-2.6.

| Dimension Tolerance Range |           |
|---------------------------|-----------|
| Dimension                 | Tolerance |
| ≤ 1                       | ±0.10     |
| >1 ~ 2                    | ±0.12     |
| >2 ~ 3                    | ±0.14     |
| >3 ~ 4                    | ±0.16     |
| >4 ~ 6                    | ±0.18     |
| >6 ~ 12                   | ±0.20     |
| >12~19                    | ±0.23     |
| >19~25                    | ±0.25     |
| >25~38                    | ±0.30     |
| >38~50                    | ±0.36     |
| >50~100                   | ±0.61     |
| >100~150                  | ±0.86     |
| >150~200                  | ±1.12     |
| >200~250                  | ±1.37     |
| Angle tolerance±1°        |           |

|          |  |                         |     |                      |       |        |                 |                         |      |                 |                     |      |  |
|----------|--|-------------------------|-----|----------------------|-------|--------|-----------------|-------------------------|------|-----------------|---------------------|------|--|
| Mold CAT |  | AREA (mm <sup>2</sup> ) |     | Theory Weight (kg/m) | 15.95 | Name   |                 | Unmarked Round Corner   |      | Required Length |                     | Fax  |  |
| Alu-Rod  |  | Ratio                   | 1:1 | Primeter (mm)        |       | Drawer |                 | Unmarked Thickness (mm) | ±0.3 | Material        | 6063-T5             | Date |  |
| Mold DIM |  | Mold Pad                |     |                      |       | Phone  | +86 13003437887 |                         |      | Website         | www.dongyan-alu.com |      |  |